



Specialist in Architectural Glass Systems

**Summarised Loads Chart
EazyFit 1.5k 200MM Centres**

Fixings Used For Testing

Concrete Expansion Anchor Wurth ANC-(W-HAZ/S)-(A2K)-10-M8X87
 M12 Steel Bolts M12 x 40 Fully Threaded

Not Suitable ■
 Suitable ■

Glass Thickness	12mm Toughened		13.5mm SGP Laminate		15mm Toughened		17.5mm Toughened PVB Laminate		19mm Toughened	21.52mm Toughened PVB Laminate		21.52mm Sentry Laminate	
	1100mm	1200mm	1100mm	1200mm	1100mm	1200mm	1100mm	1200mm	1100mm	1100mm	1350mm	1100mm	1200mm
Load requirement													
0.36kn/mtr Base Mounted	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
0.36kn/mtr Side Mounted	Green	Green	Green	Red	Green	Green	Green	Green	Green	Green	Green	Green	Green
0.74kn/mtr Base Mounted	Red	Red	Red	Red	Green	Red	Green	Red	Green	Green	Green	Green	Green
0.74kn/mtr Side Mounted	Red	Red	Red	Red	Green	Red	Red	Red	Green	Green	Red	Green	Green
1.5kn/mtr Base Mounted	Red	Red	Red	Red	Red	Red	Red	Red	Green	Red	Red	Green	Green
1.5kn/mtr Side Mounted	Red	Red	Red	Red	Red	Red	Red	Red	Green	Red	Red	Green	Red

Full Test reports available by request.